

QubePos®



QP-Q260

Thermal Receipt Printer

- Fast versatile printing up to 260mm per second
- Drop in paper loading and with auto Cutter
- Horizontal or Wall-hanging installation
- Queue function available



Restaurant



Shopping



Mart



Lan




Bluetooth



QP-Q260

Thermal Receipt Printer



Specification

MODEL	QP-Q260
Printing method	Direct thermal
Printing speed	260mm/s
Black mark detection	Support
Network monitoring	Support
Roll paper	79.5 ± 0.5mm
Column capacity	576 dots/line or 512 dots/line
Character size	ANK, Font A: 12 x 24 dots Font B: 9 x 17 dots simplified/traditional Chinese: 24 x 24 dots
Command	Compatible with ESC/POS
Interface (Optional)	Serial+USB+LAN, USB+Parallel
Auto cutter	Partial
Reliability	Printing head life 100 km
Barcode	UPC-A/ UPC-E/ JAN13 (EAN13)/ JAN8 EAN8)/ CODE39/ ITF/ CODABAR/ CODE93/ CODE128
Auto cutter	Full or Partial (optional)
2D Bar code	QR CODE/PDF417
NV flash	256k Bytes
Input buffer	2048k Bytes
Paper thickness	0.06-0.08mm
Adaptor input voltage	AC 110V/220V, 50-60Hz
Power supply	DC 24V = 2.5A
Printer input voltage	DC 24V = 2.5A
Cash drawer control	DC 24V = 1A
Working environment	Temperature (0~45°C), humidity (10~80%)
Storage environment	Temperature (-10~60°C), humidity (10~90%)
Drivers	Win 9X/Win 2000/Win 2003/Win XP/Win 7/ Win 8/Win 10/LinuxWin 10/Linux

*Due to Qube Apps Solutions continuing product improvement programs, specifications and features are subjected to change without prior notices.



QUBE APPS SOLUTIONS SDN. BHD. (981542-A)

No.2-32A1, Jalan Desa 1/1, Desa Aman Puri, Kepong,
52100 Kuala Lumpur, Malaysia.

Tel : +603-6262 5182, +603-6262 5162

Fax : +603-6272 5162

Website : www.qubeapps.com

