

ACT A-1560 (G)

The ACT is an Android-based force with the latest Android 12 version that enables secure and efficient device management with GMS certification and SOTI certification, a mobile device management solution. It also houses the latest processors from Intel, a Windows operating system, for efficient performance. With a 15.6 widescreen, the ACT boasts a slim, edgy design.



Android / Intel's Latest Processors



Slim Design, Modern Interior Design



Bezel-Free Display Utilizable Interface



15.6-inch PCAP Touch Display



Fast Installation/ Maintenance




Compact Size to Save Space



Plenty of I/O Ports Support



Distribution, Restaurant, Franchise Industry



ACT A-1560 (G) Specification

ACT A-1560 (G)

System

Processors	RK3399 Dual-core Cortex-A72 up to 1.8GHz Quad-core Cortex-A53 up to 1.4GHz
Memory	4GB Standard, DDR4, On-board
Storage	eMMC 32GB, On-board (Max. 256GB)
Operating Systems	Android 12
Audio	HD Audio Codec

Display

Type	15.6" TFT LCD, LED Backlight (eDP Interface), Projected Capacitive Touch
Resolution	1920 x 1080
Brightness	300 cd/m ²

Interface

Display	1 x Displayport, MiniDP (Only compatible with ACT-only products)
USB	Rear 5 (4 x USB 2.0, 1 x USB-C)
Serial	External 2 COM1 RJ45 , Full Signal COM3 MiniDP, Only TX/RX, 12V Power Output, Reserved for CDP Internal 1 COM2 FPC Connector , Only TX/RX, Reserved for MSR
Cash Drawer Port	1 x Cash Drawer Port [RJ-12, 6 Pins(GPIO Communication)]
WIFI / BT	BT(V4.0)+ WLAN (802.11 a/b/g/n, 2.4G/5G) combo module, On-board (Factory Option)
LAN	1 x Gigabit Ethernet , RJ-45
Audio & Speaker	1 x Line-out / 1W (Mono)
Power DC-IN	4 Pin DIN Jack

Power

Power Supply	Adapter 12V, 5A(4 Pin Din Jack)
--------------	---------------------------------

Options & Peripherals

2nd Displays	10.1" (1280 x 800) LCD Display, Optional Touchscreen
External IO Box	Option 1: 2 x 12V Powered USB 2.0 / 1 x 24V Powered USB 2.0 / 2 x RJ45 (Full Signal) Option 2: 1 x 12V Powered USB 2.0 / 1 x 24V Powered USB 2.0 / 2 x USB 2.0 / 2 x RJ45 (Full Signal) Option 3: 1 x 24V Powered USB 2.0 / 4 x USB 2.0 / 2 x RJ45 (Full Signal) Option 4: 6 x USB 2.0 / 2 x RJ45 (Full Signal) One option attachable at a time
Wall Mount Kit	TBD
Conversion Cable	RJ-45 to D-sub 9

* The product pictures and display contents in the above pages are for illustration purpose only. The actual product effects (including but not limited to appearance, color, size) and screen display contents (including but not limited to background UI pictures) might differ.



Qube Apps Solution Sdn Bhd

No.2-30B, Jalan Desa 1/1, Desa Aman Puri, 52100 Kuala Lumpur, Wilayah Persekutuan.

Office No : +603-6262 5182 | Mobile No : +6010-8825182 | Reach Us at enquiry@qubeapps.com

